



ENHANCED RELIABILITY

Low Maintenance gauge operated by anyone in less than 10 mins.
Easily installed/retrieved with standard kick-over tool.

METROLOG BREAKTHROUGH

Tubing or annulus pressure can be monitored with the same gauge.
Smart battery system displays the remaining power of your cells.
Design based on a standard gas lift valve.

APPLICATIONS

For well diagnosis and all fast temperature transient needs.
For long term monitoring (up to 6 months) with no flow restriction.

SPECIFICATIONS

PRESSURE	<i>PiezoResistive Sensor</i>
Range	0-1500 up to 0-15000 psi (0-100 to 0-p1000 bar)
Accuracy	± 0.05% FS
Resolution	<0.05 psi (<0.003 bar)
TEMPERATURE	<i>PT100</i>
Range	0 to 300 °F (-20 to 150 °C)
Accuracy	± 0.6 °F (0.3 °C)
Resolution	<0.01 °F (<0.005 °C)
MECHANICS	
Material	17-4 PH aged to fit sour service (H ₂ S, CO ₂ , acid) and Stainless Steel
OD	1" (25 mm)
Length	19" (48 cm)
Weight	1.25 lbs (0.75 kg)
Latch	BK type
V-Packing	Adapted to ported gas lift mandrels
MEMORY	
Capacity	1 400 000 points
COMPUTER AND SOFTWARE	
Programming Modes	Conventional, Advanced
Parameters	1s-18h, Scanning Rate, Time delay, Pressure start (Trigger, Threshold)
Windows	Compatible with Windows 2000/XP/Vista
Connector	RS232/USB
BATTERY TYPE	
2L15E	For up to 180 days of operation

Metrolog

Technoparc. Bat.2. Avenue L'occitane. BP 27415. 31674 Labège Cedex France
Telephone: (33) 5 61 34 80 74. **Fax:** (33) 5 61 20 41 31. **E-mail:** sales@metrolog.com
www.metrolog.com

Sercel

S.A. au capital de 2 000 000 €. Siège Social: 16 rue de Bel-Air 44470 Carquefou.
 378.040.497 R.C.S. Nantes. Code APE 2651B
www.sercel.com

Printed in France. © Sercel 09/08 - Information subject to change without notice. TDS0_024_A