MEMORY GAUGE FOR SIDE POCKET MANDRELS

Designed to fit into 1" SPM to replace Gas Lift Valves or Dummy Valves

// ENHANCED ELECTRONIC PERFORMANCES

- Low Maintenance gauge operated by anyone in less than 10 mins.
- Easily installed/retrieved with standard kick-over tool.

// INNOVATIVE BREAKTHROUGH / BENEFITS

- Design based on a standard gas lift valves.
- Electronics with 4 times redundant memories.
- Tubing or annulus pressure can be monitored with the same gauge.
- •Smart battery system displays the remaining power of your cells.

// APPLICATIONS

- For well diagnosis and all fast temperature transient needs.
- For long term monitoring (up to 6 months) with no flow restriction.



MEMORY GAUGE FOR SIDE POCKET MANDRELS

Designed to fit into 1" to replace Gas Lift Valves or Dummy Valves

METROLOGY

Name	Side Pocket 1"	
Pressure PiezoResistive Se	nsor	
Range	From atm. pressure to 1.5kpsi up to 15kpsi (Atm. to 100 up to 1000 bar)	
Accuracy	± 0.05% FS	
Resolution	<0.05 psi (<0.005°C)	
Temperature PT100		
Operating Range*	0 to 300°F (-20 to 150°C)	
Accuracy	± 0.6°F (± 0.3°C)	
Resolution	<0.01°F (<0.005°C)	
Battery Type		
For up to 180 days of operation	X15	

*Calibrated range starts at ambiant temperature (20°C) Calibration down to -20°C available on demand

Mechanics	1" SPM
Material	17-4 PH aged to fit sour service (H ₂ S, CO ₂ , Acid) and Stainless Steel
OD	1" (25 mm)
Length	19" (48 cm)
Weight	1.25 lbs (0.75 kg)
Latch	BK type
V-Packing	Adapted to standard gas lift mandrels
Pressure monitoring	Tubing or Annulus

Computer & Software	
Programming modes	Conventional, Advanced
Parameters	1s-18h, Scanning Rate, Time delay, Pressure start (Trigger, Threshold)
Windows	Compatible from Windows 2000 to Windows 10
Connector	USB
Memory Capacity	4.2M data points of pressure and/or temperature

Metrolog

1110 Av. L'Occitane. Technoparc. Bat. 2 C.S. 17619

31676 LABEGE Cedex France

Tél: (33) 5 61 34 80 74 - Fax: (33) 5 61 20 41 31

E-mail: sales@metrolog.com

Information subject to change without notice. TDSO_071_AB

www.metrolog.com

